



CONNECTOR & CABLE ACCESSORIES

STRAIN RELIEF SPECIFICATIONS

LIGHT DUTY



MEDIUM DUTY



HEAVY DUTY




TABLE I – DIMENSIONAL CHART – FOR STRAIN RELIEF ADAPTERS IN (MM)

DASH **	T MAX	U MAX	V MAX	W MAX	Y MAX	Z MAX
01	.780 (19.8)	1.375 (34.9)	957 (24.3)	.437 (11.1)	.812 (20.6)	.812 (20.6)
02	.780 (19.8)	1.375 (34.9)	1.145 (29.1)	.437 (11.1)	.875 (22.2)	.937 (23.8)
03	.780 (19.8)	1.375 (34.9)	1.332 (33.8)	.500 (12.7)	1.062 (27.0)	1.062 (27.0)
04	.780 (19.8)	1.375 (34.9)	1.332 (33.8)	.563 (14.3)	1.156 (29.4)	1.188 (30.2)
05	.811 (20.6)	1.437 (36.5)	1.551 (39.4)	.563 (14.3)	1.250 (31.8)	1.312 (33.3)
06	.905 (23.0)	1.437 (36.5)	1.770 (45.0)	.563 (14.3)	1.469 (37.3)	1.562 (39.7)
07	1.092 (27.7)	1.562 (39.7)	2.113 (53.7)	.656 (16.7)	1.688 (42.9)	1.750 (44.5)
08	1.124 (28.5)	1.812 (46.0)	2.363 (60.0)	.656 (16.7)	2.031 (51.6)	2.250 (57.2)
09	1.399 (35.5)	2.062 (52.4)	2.770 (70.4)	.656 (16.7)	2.281 (57.9)	2.375 (60.3)
10	1.399 (35.5)	2.062 (52.4)	3.020 (76.7)	1.188 (30.2)	2.688 (68.3)	2.625 (66.7)
11	N/A	2.188 (55.6)	N/A	1.187 (30.1)	2.938 (74.6)	2.812 (71.4)
12	N/A	N/A	N/A	1.125 (28.6)	3.500 (88.9)	N/A

TABLE II – CABLE RANGE – FOR STRAIN RELIEF ADAPTERS IN (MM)

DASH	STYLE 'H'		STYLE 'A'		STYLE 'C'	
	MIN	MAX	MIN	MAX	MIN	MAX
01	.125 (3.2)	.312 (7.9)	.156 (4.0)	.250 (6.4)	.217 (5.5)	.219 (5.6)
02	.250 (6.4)	.437 (11.1)	.188 (4.8)	.312 (7.9)	.296 (7.5)	.312 (7.9)
03	.312 (7.9)	.562 (14.3)	.281 (7.1)	.438 (11.1)	.390 (9.9)	.438 (11.1)
04	.350 (8.9)	.625 (15.9)	.387 (9.8)	.562 (14.3)	.434 (11.0)	.531 (13.5)
05	.500 (12.7)	.750 (19.1)	.375 (9.5)	.625 (15.9)	.434 (11.0)	.625 (15.9)
06	.625 (15.9)	.937 (23.8)	.438 (11.1)	.750 (19.1)	.596 (15.1)	.750 (19.1)
07	.875 (22.2)	1.250 (31.8)	.625 (15.9)	.938 (23.8)	.596 (15.1)	.938 (23.8)
08	1.000 (25.4)	1.375 (34.9)	.875 (22.2)	1.250 (31.8)	.858 (21.8)	1.250 (31.8)
09	1.250 (31.8)	1.625 (41.3)	1.000 (25.4)	1.375 (34.9)	.858 (21.8)	1.375 (34.9)
10	1.437 (36.5)	1.875 (47.6)	1.250 (31.8)	1.625 (41.3)	1.107 (28.1)	1.625 (41.3)
11	N/A	N/A	1.437 (36.5)	1.875 (47.6)	1.421 (36.1)	1.875 (47.6)
12	N/A	N/A	1.875 (47.6)	2.375 (60.3)	N/A	N/A